Traclite Controller Enquiry form V1 Quote Request Order Customer Details Date: Company: Contact name: Tel No: Fax No: Email: Project Ref: Requested delivery date: Purchase Order No: Delivery Address (Including Postal Code):

Basic Data	Supply Voltage:		Phase:	— Neutral: Yes □ - No □
	Number of floors:	N	Max 8 stops for Trac	clite
	Speed: m/s Max 1.6M/s for Traclite			
	Main homing floor:		Fire floor:	
	Full collective:	Down c	ollective:	Non selective collective:
	Simplex:	Duplex:		
	Motor room position:	Above:	Below:	Travel: m
General Notes				

Lifteknic Limited 11 Victoria Road, Chester CH2 2AX Tel: +44(0)1244 389690

Traclite Controller Enquiry form V1

Motor Data				
	Manufacture: Model:			
	Max starting current:	Amps	KW:	HP:
	Full load running current: Amps Max 29AMP 13Kw for Traclite			P 13Kw for Traclite
	Fan control: Yes 🗆 - No 🗆			
	Fan supply voltage:	Amps:		Phase:
Motor Encoder	Open Loop:	Closed Loop:		
	Manufacture:	Model:	Supply:	Volts PPR:
Brake Information	Voltage:dc		Power:	Watts
	Brake contacted fitted: Yes □ - No □ N/O: □ - N/C: □			
	Resistance: Ohms	Power:	Watts	Hold voltage: volts
Door Information	Car safety edge:	□ N/O	□ N/C	Supply: Vac/Vdc
	Existing power car & landing:		Existing power	er car & manual landing: \square
	Existing manual car & landing:			
	Manufacturer: Model:			
	Type:			
	Advance door opening: Door nudging: Zone locking:			ne locking:
	No of car entrances:	Thru car:	☐ Sta	ggered:

Traclite Controller Enquiry form V1

Call Buttons	Landing pushes by Lifteknic Limited: see options Car pushes by Lifteknic Limited: see options				
	No of landing call button risers:				
	Existing landing call push voltage: volts LED: Lamp: L				
	Existing car push voltage: volts LED: Lamp: L				
Landing Indicators	Landing digital indicators: Yes □ - No □				
	Landing position indicators by Lifteknic : (see options – includes arrival gong & hall lantern)				
	By others : Yes Encoder : Yes*				
	Hall lanterns by others (Included on Lifteknic indictor)				
	External : Yes On Encoder : Yes On Encoder: Yes*				
	Arrival gong (speaker): Yes — No — (Included with Lifteknic indictor)				
	Landing :				
	*Please provide details in notes				
Car Indicator	Car position indicators by Lifteknic: (see options – includes hall lantern)				
	By others : Yes ☐ Encoder : Yes* ☐				
	*Please provide details in notes				
*Indicator Notes	Floor Markings				

Fax: +44(0)1244 389691

Traclite Controller Enquiry form V1

Miscellaneous	Lifteknic position encoder system:	☐ Yes	PSE [On car	☐ c	n governor		
	Lifteknic Tapehead:	☐ Yes						
	Shaft Switches:	☐ Yes		Bi-stable Magnet switches				
	Cartop Control Station	☐ Yes	□ No	Pre wired Unit	with	n RCD socket		
	EMOP Pendant	☐ Yes	Emergency Electrical Operation (Panel test)					
	Halfway Terminal Box:	☐ Yes	es No Top of car terminals					
	Speech synthesiser:	eech synthesiser: Yes List any special message speech notes			ssages in			
	Handwinding position indicator:				PSE system			
	HMMI on cabinet door panel:	☐ Yes	□ No	Jo				
	Standard Items Included							
	Service control:	✓ Yes						
	Handwind floor level indicator:	✓ Yes	Buzzer an	d Lamp Include	d			
	LCD H.M.I:	✓ Yes						
	Trip counter:	✓ Yes	es					
	Door close push:	✓ Yes						
	Load weighing 90% & 110%:	✓ Yes	(Overload indication included with indicator and speech unit)					
	Fire control/Alarm return:	✓ Yes	☑	BS5655	☑	BS5588		
Speech Notes:								

Lifteknic Limited 11 Victoria Road, Chester CH2 2AX

Tel: +44(0)1244 389690

Traclite Controller Enquiry form V1

Options	Qty				
		Shaft limit switch set (kit includes limit switches and fitting kit)			
		Qube 7000 Surface mount LOP – Push button and call acceptance beeper			
		Qube 7000N Surface mount LOP – Push button and call acceptance beep			
		Up Push Qty: Twin Push Qty:			
		Qube 7000 Surface mount Dot Matrix Red LED indicator and gong			
		Qube 7000N Surface mount LCD Blue indicator and gong			
		Qube 9000 Surface mount LCD Blue indicator and gong			
		Car trailing Flex for CAN network 20 std + 2 twisted pairs 40 metre length			
		Car trailing Flex for CAN network 20 std + 2 twisted pairs 55 metre length			
		Car trailing Flex standard 24 way 40 metre length			
		Car trailing Flex standard 24 way 55 metre length			
		(1 x Twisted Pair and 2 x 24 Way required for Traclite)			

Fax: +44(0)1244 389691